

UNIVERSITY
OF
CALIFORNIA

First
For UC

Now through June 30th

Exclusive UC pricing on Thermo Scientific TSX ultra-low freezers

Price includes 5 year bumper to bumper coverage on the 12 year warranty!* In addition, for each rack you purchase, get a second rack for free up to the freezer's capacity.**

A potential combined savings of over \$5,500!

Lifetime V-Drive variable speed compressor warranty**

- Best peak variation of energy-efficient ultra-low freezers: less than 5°C
- Fastest door opening recovery on the market: 17 minutes
- 0.85°C steady-state temperature variation over time
- Best overall temperature uniformity: < 5.2°C with door openings, < 4.0°C with no door openings
- Longest warm-up time from -80°C to -50°C at 5.05 hours
- Four capacities: 400, 500, 600 and 700 2-inch box

Freezers are eligible for PG&E rebates: \$300 for TSX400; \$600 on all other sizes. Proof of purchase required.

* Lifetime of the compressor is 12 years. Lifetime compressor warranty is void if the unit is not maintained as set forth in the operation and service manuals. U.S. only.

** Offer is valid in the United States only. January 1 through June 30, 2018. Customer acknowledges that this offer may include a discount or other price reduction that must be properly and accurately accounted for and reported by customer in accordance with all federal and state laws, including without limitation the federal anti-kickback law (42 C.F.R. § 1320a-7b(b)(3)(A)) and regulations thereunder (42 C.F.R. §1001.952(h)).



**Contact your Fisher Scientific
representative today!**

Name

Email

Phone

Thermo Scientific TSX Series Upright Freezers (-50°C to -86°C)

Model No.	Capacity		Electrical	Amps/breaker (plug)	Shipping weight lbs. (kg)	Interior dimensions H x W x D in. (cm)	Exterior dimensions H x W* x D in. (cm)	Pricing
	cu. ft. (liters)	2" cryobox						
TSX40086A5BB	19.4 (549)	400	115V / 60Hz	9.0/15 (NEMA 5-15)	665 (302)	51.2 x 23.1 x 28.3 (130.1 x 58.8 x 71.9)	78.0 x 28.3 x 37.6 (198.1 x 71.9 x 95.5)	\$10,399
TSX50086A5BB	24.1 (682)	500	115V / 60Hz	9.5/15 (NEMA 5-15)	721 (327)	51.2 x 28.8 x 28.3 (130.1 x 73.0 x 71.9)	78.0 x 34.0 x 37.6** (198.1 x 86.4 x 95.5)	\$10,899
TSX60086A5BB	28.8 (816)	600	115V / 60Hz	8.5/15 (NEMA 5-15)	790 (358)	51.2 x 34.4 x 28.3 (130.1 x 87.3 x 71.9)	78.0 x 39.6 x 37.6** (198.1 x 100.6 x 95.5)	\$11,399
TSX70086A5BB	33.5 (949)	700	115V / 60Hz	10.6/15 (NEMA 5-15)	894 (406)	51.2 x 40.0 x 28.3 (130.1 x 101.6 x 71.9)	78.0 x 45.2 x 37.6** (198.1 x 114.8 x 95.5)	\$12,875

TSX Series Racks For each rack you purchase, get a second one free up to freezer's capacity

Model No.	Description	Dimensions H x W x D in. (cm)	Storage	Dimensions H x W x D in. (cm)			
				TSX400	TSX500	TSX600	TSX700
1950520	Adjustable Side Access Rack for 2" Boxes	11.6 x 5.4 x 26.75 (29.5 x 13.7 x 67.9)	Boxes per rack	25	25	25	25
			Racks per shelf	4	5	6	7
			Racks per freezer	16	20	24	28
			Boxes per freezer	400	500	600	700
1950521	Adjustable Side Access Rack for 3" Boxes	11.9 x 5.5 x 26.9 (30.2 x 14 x 68.3)	Boxes per rack	15	15	15	15
			Racks per shelf	4	5	6	7
			Racks per freezer	16	20	24	28
			Boxes per freezer	240	300	360	420

Thermo Scientific Revco RLE Upright Freezers (-50C to -86C)

Model No.	Capacity		Electrical	Amps/breaker (plug)	Shipping weight lbs. (kg)	Interior dimensions H x W x D in. (cm)	Exterior dimensions H x W* x D in. (cm)	Pricing
	cu. ft. (liters)	2" cryobox						
RLE50086A5BB	24.1 (682)	500	115V / 60Hz	9.5/15 (NEMA 5-15)	721 (327)	51.2 x 28.8 x 28.3 (130.1 x 73.0 x 71.9)	78.0 x 34.0 x 37.6** (198.1 x 86.4 x 95.5)	\$8,399
RLE60086A5BB	28.8 (816)	600	115V / 60Hz	8.5/15 (NEMA 5-15)	790 (358)	51.2 x 34.4 x 28.3 (130.1 x 87.3 x 71.9)	78.0 x 39.6 x 37.6** (198.1 x 100.6 x 95.5)	\$8,895

Revco Racks For each rack you purchase, get a second one free up to freezer's capacity

Model No.	Description	Dimensions H x W x D in. (cm)	Storage	Dimensions H x W x D in. (cm)	
				RLE500	RLE600
1950518	Adjustable Side Access Rack for 2" Boxes	11.6 x 5.4 x 26.75 (29.5 x 13.7 x 67.9)	Boxes per rack	20	20
			Racks per shelf	5	6
			Racks per freezer	25	30
			Boxes per freezer	500	600
1950519	Adjustable Side Access Rack for 3" Boxes	11.9 x 5.5 x 26.9 (30.2 x 14 x 68.3)	Boxes per rack	15	15
			Racks per shelf	5	6
			Racks per freezer	25	30
			Boxes per freezer	300	360

Options (Field installed must be installed by a qualified professional)

Product	Installation	400 box	500 box	600 box	700 box
LN₂ Backup System: Maintains temperature down to -80°C with liquid nitrogen. Models for RLE300 are stand alone	Factory Installed	LN4567	LN4567	LN4567	LN4567
	Field Installed	FLN4567LE	FLN4567LE	FLN4567LE	FLN4567LE
CO₂ Backup System: Maintains temperature down to -67°C with CO ₂ . Models for RLE300 are stand alone	Factory Installed	CO4567	CO4567	CO4567	CO4567
	Field Installed	FCO4567LE	FCO4567LE	FCO4567LE	FCO4567LE
Chart Recorder (Inkless): 6" (15.2 cm), seven day inkless recorder, -115° to +50°C, +5°C resolution	Factory Installed	CR400TSXLE	CR500TSXLE	CR600TSXLE	CR700TSXLE
	Field Installed	FCR400TSXLE	FCR500TSXLE	FCR600TSXLE	FCR700TSXLE
Chart Recorder (Ink): 6" (15.2 cm), seven day inkless recorder, -115° to +50°C, +5°C resolution	Factory Installed	CRP400TSXLE	CRP500TSXLE	CRP600TSXLE	CRP700TSXLE
	Field Installed	FCRP400TSXLE	FCRP500TSXLE	FCRP600TSXLE	FCRP700TSXLE

Ask your Fisher Scientific sales representative about additional freezer options and accessories.



In the United States:

For customer service, call 1-800-766-7000

To fax an order, use 1-800-926-1166

To order online: fishersci.com

For Research Use Only. Not for use in diagnostic procedures. © 2018 Thermo Fisher Scientific Inc. All rights reserved. The ENERGY STAR name and logo are trademarks of the U.S. EPA. All other trademarks are the property of Thermo Fisher Scientific and its subsidiaries unless otherwise specified. **0118**